



Ancien code	Code de commande	A BSP	Dimensions en mm					Couple de Serrage (Nm)	Masse Kg	Code joint fibre*
			B	C	D	E	CH			
A4-301	118.014.SLNS	1/4"	20	15	17	8	17	0,002	0,002	480.FIB.01400
A4-302	118.038.SLNS	3/8"	22	14	6,5	10,5	18	0,003	0,003	480.FIB.03800
A4-303	118.012.SLNS	1/2"	28	16	8	11	24	0,005	0,005	480.FIB.01200
A4-304	118.034.SLNS	3/4"	35	21	8	12	30	0,008	0,008	480.FIB.03400
A4-305	118.100.SLNS	1"	43	32	11	12	35	0,014	0,014	480.FIB.10000
A4-306	118.114.SLNS	1"1/4	51	33	10	16	42	0,017	0,017	480.FIB.11400
A4-307	118.112.SLNS	1"1/2	58	40	10	20	50	0,047	0,047	480.FIB.11200
A4-308	118.200.SLNS	2"	74	48	12	20	64	-	-	480.FIB.20000

201

Spécifications :

Matière : Résine polyamide transparente haute densité

* joint fibre à commander séparément

Température d'utilisation jusqu'à 100°C

Pression de service : 3 bar

