



Code de commande	Ancien code	DIN	A	Dimensions en mm					Vis CHC Classe 8.8	O-Ring 70 shore	Pression de service (bar)
				Ø	B	C	D	E			
<b>200.203.A3510</b>	<b>B10-000</b>	10L	M16x1,5	10	35	40	18	11,5	M6x20-M6x35	3075	300
<b>200.203.A3512</b>	<b>B10-001</b>	12L	M18x1,5	12	35	40	18	11,5	M6x20-M6x35	3075	300
<b>200.203.A3515</b>	<b>B10-002</b>	15L	M22x1,5	15	35	40	18	11,5	M6x20-M6x35	3075	300
<b>200.203.A3516</b>	<b>B10-003</b>	16S	M24x1,5	16	35	40	18	11,5	M6x20-M6x35	3075	300
<b>200.203.A4015</b>	<b>B10-004</b>	15L	M22x1,5	15	40	44	24	13	M6x25-M6x45	132	100
<b>200.203.A4018</b>	<b>B10-005</b>	18L	M26x1,5	18	40	40	24	13	M6x25-M6x45	132	100
<b>200.203.A4020</b>	<b>B10-009</b>	20S	M30x2	20	40	40	24	13	M6x25-M6x45	132	100
<b>200.203.A4022</b>	<b>B10-006</b>	22L	M30x2	22	40	40	24	13	M6x25-M6x45	132	100
<b>200.203.A4028</b>	<b>B10-007</b>	28L	M36x2	28	40	40,5	28	16	M6x25-M6x45	132	100
<b>200.203.A4035</b>	<b>B10-008</b>	35L	M45x2	35	40	41,5	32	16	M8x25-M8x50	132	100
<b>200.203.A5520</b>	<b>B10-020</b>	20S	M30x2	20	55	54	34	13	M8x25-M8x60	4118	250
<b>200.203.A5525</b>	<b>B10-010</b>	25S	M36x2	25	55	54	34	13	M8x25-M8x60	4118	250
<b>200.203.A5530</b>	<b>B10-011</b>	30S	M42x2	30	55	54	34	13	M8x25-M8x60	4118	250
<b>200.203.A5538</b>	<b>B10-013</b>	38S	M52x2	38	55	52	43	12	M8x25-M8x70	4118	200
<b>200.203.A5542</b>	<b>B10-014</b>	42L	M52x2	42	55	52	43	12	M8x25-M8x70	4118	100

Spécifications :

Matière : Acier zingué

Livré avec vis, rondelles et joint O-Ring

Informations DIN "L" et DIN "S" : Voir page 156

