



Code de commande	Ancien code	DIN	A	millimètres					Vis CHC Classe 8.8	O-Ring 70 shore	Pression de service (bar)
				Ø	B	C	D	E			
<b>200.203.R3510D</b>	<b>B9-001</b>	10L	M16x1,5	10	35	46	8	30	M6x20	3075	315
<b>200.203.R3512D</b>	<b>B9-002</b>	12L	M18x1,5	12	35	46	8	30	M6x20	3075	315
<b>200.203.R3515D</b>	<b>B9-003</b>	15L	M22x1,5	15	35	46	8	30	M6x20	3075	250
<b>200.203.R3516D</b>	<b>B9-011</b>	16S	M24x1,5	16	35	46	8	30	M6x20	3075	315
<b>200.203.R4015D</b>	<b>B9-012</b>	15L	M22x1,5	15	40	52	8	35	M6x20	3100	100
<b>200.203.R4018D</b>	<b>B9-004</b>	18L	M26x1,5	18	40	52	8	35	M6x20	3100	100
<b>200.203.R4020D</b>	<b>B9-013</b>	20S	M30x2	20	40	52	8	35	M6x20	3100	250
<b>200.203.R4022D</b>	<b>B9-005</b>	22L	M30x2	22	40	52	8	35	M6x20	3100	100
<b>200.203.R4028D</b>	<b>B9-006</b>	28L	M36x2	28	40	52	8	40	M6x20	3100	100
<b>200.203.R5520D</b>	<b>B9-007</b>	20S	M36x2	20	55	70	12	50	M8x25	3125	250
<b>200.203.R5525D</b>	<b>B9-008</b>	25S	M36x2	25	55	70	12	50	M8x25	3125	250
<b>200.203.R5530D</b>	<b>B9-009</b>	30S	M42x2	30	55	70	12	50	M8x25	3125	250
<b>200.203.R5535D</b>	<b>B9-010</b>	35L	M45x2	35	55	70	12	50	M8x25	3125	100

120



Spécifications :

Matière : Acier zingué

Livré avec vis, rondelles et joint O-Ring

Informations DIN "L" et DIN "S" : Voir page 156